

RECKON CLEANER

INJECTION PUMP CLEANER/PRIMER

DESCRIPTION

RECKON CLEANER is a non-flammable, solvent-free fluid used to clean out the lines of polyurethane grout injection equipment. RECKON CLEANER can also be left in the pump lines as a primer.

PRIMARY APPLICATIONS

- Injection pump cleaner
- Priming lines of injection pumps

FEATURES/BENEFITS

- Non-flammable, non-corrosive
- Contains no solvents
- Thoroughly cleans urethane grouting equipment, ensuring a moisture-free injection system

TECHNICAL INFORMATION

TYPICAL PROPERTIES	RESULTS
Specific Gravity @ 77°F (25°C)	0.96
Viscosity @ 77°F (25°C)	122 cps
Flash Point	450°F (232°C)

PACKAGING

RECKON CLEANER is packaged in (30 L) drums.

SHELF LIFE

RECKON CLEANER has a shelf life of 3 years in original, unopened containers.

DIRECTIONS FOR USE

Pour RECKON CLEANER into both A side and B side pump tanks. Use a scrub rush to remove any grout residue from the sides or bottom of tanks. Dispense The RECKON CLEANER through hoses into an appropriate waste receptacle. Add clean RECKON CLEANER into the pump and prime the lines, leaving the RECKON CLEANER in the pump until the next project. Be sure to expel all RECKON CLEANER from the lines prior to the next grouting job, because remaining material will affect the curing capability of urethane grouts.

PRECAUTIONS/LIMITATIONS

- In all cases, consult the Safety Data Sheet before use.

QUALITY STATEMENT

All our products are manufactured to comply with our internal QA/QC program and quality management system to ensure consistency and quality

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their applications are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that the Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.

NOTE

The information included on this Technical Data Sheet is the sole property of Reckon Chemicals Pvt Ltd. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

WARRANTY: The Reckon Chemicals (Pvt.) Ltd. (Reckon) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Reckon, no other representations or statements made by Reckon or its representatives, in writing or orally, shall alter this warranty. Reckon MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Reckon product fails to conform with this warranty, Reckon will replace the product to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Reckon does not authorize anyone on its behalf to make any written or oral statements which in any way alter Reckon's installation information or instructions in its product literature or on its packaging labels. Any installation of Reckon products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Reckon's products for the Buyer's intended purposes.

RECKON CHEMICALS PRIVATE LIMITED
21 CCA, BLOCK B, KHAYABAN-E-AMIN, LAHORE
Tell: +92-42-35452620, +92-42-35230419
Web: www.reckonchemicals.com
Email: Info@reckonchemicals.com

