

REC FIBER BOARD

BITUMEN IMPREGNATED FIBERBOARD

DESCRIPTION

REC FIBER BOARD is a compressible sheet manufactured from bitumen impregnated wood fibers. It is a non-extruding, compressible joint filler to form and fill expansion and isolation joints for in-situ and pre-cast concrete construction. Fiberboard can also be used as a protection board to protect waterproofing systems against mechanical damage.

PRIMARY APPLICATIONS

REC FIBERBOARD can be used as:

- Expansion joints filler in concrete pavements, walls and suspended slabs.
- As a filler for joints in roads, runways and bridges.
- Protection board for waterproof, coatings, and membranes.
- For structural isolation joints.

FEATURES/BENEFITS

- Excellent recovery.
- Low distortion.
- Easy to cut and handle.
- Will not extrude under compression.
- Rot-Proof.

STANDARDS

REC FIBERBOARD complies with DTp Specification for Highway Works, Dec 1991 series 1000 clause 1015.

DIRECTIONS FOR USE

AS JOINTS FILLER:

- Fiberboard shall be placed against the shuttering on the concreting side before the pour begins. Nails or suitable adhesive may be used to prevent displacement in joints in suspended slabs.

AS PROTECTION BOARD:

- Fiberboard should be fixed to the waterproofing coating or membrane using a suitable adhesive.

TECHNICAL INFORMATION

Form:	Compressible sheet
Recovery: ASTM D1751	Greater than 75%
Extrusion: ASTM D1751	Less than 1.2 mm
Distortion: ASTM D944	Less than 0.7 mm
Weathering test: DTp CI 1015	No disintegration
Brittleness: ASTM D944	Does not crack or shatter
*The above tests were carried out on 25mm thick samples.	

PACKAGING

Sheet size: 1.22 m × 2.20 m.

Thickness: 12, 18, 25 mm.

STORAGE

Store under cover, in a dry area on a flat, clean and sound surface.

HEALTH & SAFETY

- There are no health hazards associated with Fiberboard in normal use.
- For further information refer to the Material Safety Data sheet.

FIRE

- Fiberboard is flammable and will burn if exposed to flame or other sources of ignition.

WARRANTY: The Reckon Chemicals (Pvt.) Ltd. (Reckon) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Reckon, no other representations or statements made by Reckon or its representatives, in writing or orally, shall alter this warranty. Reckon MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Reckon product fails to conform with this warranty, Reckon will replace the product to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Reckon does not authorize anyone on its behalf to make any written or oral statements which in any way alter Reckon's installation information or instructions in its product literature or on its packaging labels. Any installation of Reckon products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Reckon's products for the Buyer's intended purposes.

RECKON CHEMICALS PRIVATE LIMITED
21 CCA, BLOCK B, KHAYABAN-E-AMIN, LAHORE
Tel: +92-42-35452620, +92-42-35230419
Web: www.reckonchemicals.com
Email: Info@reckonchemicals.com

