



REC TOP 113

Colored Decorative Acrylic Paint For Renovation Of Old Substrates

PRODUCT

Rec Top 113 is acrylic based high quality, color stable, decorative, weather resistant, façade paint for renovation of old substrates that are previously finished with Acrycor.

Rec Top 113 is ideal for manual applications by brush / roller. Also, Rec Top 113 can be applied by spraying machine to increase productivity and color uniformity

Rec Top 113 is acrylic emulsion paint for exterior facades which is resistant to U.V and extreme weather Conditions

ADVANTAGES

- Raw materials are selected according to the highest quality control standards.
- Exact mixing ratios and homogeneity of the blend, due to factory fully computerized production process.
- Available in wide range of uniform colors.
- Gives modern decorative finishing style.
- Excellent workability characteristics.
- The simplicity of usage and application gives very high productivity rates.
- Excellent bonding characteristics to previously applied acrycor substrates.

CHARACTERISTICS	
Color	Available in wide range of uniform colors.
Density	Approx. 1.34 kg/lit.
Hard dry	Approx. 10 hours at 23°C
Base	Acrylic copolymer water base.

* the above values may vary depending on the supplied color.

INSTRUCTIONS FOR USE

SURFACE PREPARATION

- Cement based walls and ceilings which are covered with any of Acrycor are the recommended substrates that can be renovated with Rec Top 113.
- Any problem in the substrate which may lead to water penetration must be rectified.
- All substrates should be in a good and strong condition.
- All substrates should also be clean and free from any loose particles, dust, oil, grease

PRODUCT PREPARATION

ready to use

PRODUCT APPLICATION

- Concrete painted substrates, cement based plastered walls, block walls, gypsum boards are the suitable substrates to be finished by Rec Top 113
- Scaffolding must be fixed independently to allow for one

go application.

- Rec Top 113 should be immediately applied on the well prepared substrate, while it is fresh and workable.
- Apply Rec Top 113 on to the well prepared surface either by conventional hand applied technique or using spraying machine. Ask for our line of mixers and spraying machines .
- To achieve color consistency, apply Rec Top 113 in panels and complete it around the building.
- To ensure color uniformity it is advisable to apply Rec Top 113 in the shade, not in direct sun light.
- The work force should be enough to work on large areas, to eliminate cold joints and marks between different applications, it is advisable to apply large areas in one step or split the large areas with grooved lines (Joints).
- As natural raw materials are used for the production of acrycor, it is advisable to apply the entire façade at one time to ensure color uniformity

COVERAGE RATE

1KG / 4-5 m²

1 KG / 3-4 m²

1 KG / 3-4 m²

(varies according to surface conditions, and the way of application)

PRECAUTIONS

- Do not apply Rec Top 113 on movement joints or on dynamic cracked plastered walls.
- Expansion joints should be included as per the substrate design and carried out through acrycor.
- It is advisable to seal the substrates with a suitable sealer such as Rec Lite 550 to avoid inconsistent color finish, when applied on uneven or porous surfaces

STORAGE

Shelf life is 12 months from manufacturing date, in a dry, covered storage area.

SAFETY PRECAUTIONS

While using the product, gloves, mask and goggles should be worn. Splashes to skin or eyes should be washed with clean water, in case of prolonged irritation, seek medical advice.

DISCLAIMER

while the company guarantees its product against defective materials, the use and application of these products are made without guarantee since the conditions of their application are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use and that this Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office in your location.



RECKON
CHEMICALS (PVT) LTD.

www.reckonchemicals.com
info@reckonchemicals.com

REC TOP 113

NOTE

the information included on this Technical Data Sheet is the sole property of Reckon Chemicals Pvt Ltd. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.