

REC SBR LATEX 223

SBR LATEX- BASED HIGH PERFORMANCE BONDING AGENT

DESCRIPTION

Rec SBR Latex 223 is a styrene- butadiene copolymer latex (SBR) used as a waterproof and bonding agent added to concrete and mortar

PRIMARY APPLICATIONS

- Industrial flooring
- Concrete repair
- Bonding slurries
- Watertight compartments
- Potable water reservoirs
- Cement based adhesives
- External and internal mortars

TECHNICAL INFORMATION

Appearance	White liquid
Density	1.06
PH	7 ± 1

SHELF LIFE

6 months in dry conditions and original packaging. To be stored protected against frost. In case of frost recovers its properties after progressive thawing

DIRECTION OF USE

Spatterdash keying mix

The surface must be sound, clean and free from oil and grease. In order to provide a good bonding slurry, Rec SBR Latex 223 is added with the mixing water at the ratio of 4% of cement weight. The slurry should be projected manually or sprayed mechanically. Cure with water for 3 days. Floor screed the surface must be thoroughly cleaned and free from oil and grease. Prime the substrate with a slurry made with cement, sand and REC SBR Latex 223 diluted in water (Rec SBR Latex 223 / water ratio in volume: 1/1). While the surface is still tacky, pour the concrete. The screed performances may also be improved by adding Rec SBR Latex 223 from 2 to 6 % of the cement weight. Spread the mix on the substrate and adjust it at the required level Better performances mortar Quality of cement based traditional mortars may also be improved by adding Rec SBR Latex 223 during the mix.

PACKING

REC SBR LATEX 223 is supplied in 20 liters and 200 liters

Dosage rate

2 to 6 % of cement weight for plastering mortars, enhanced mortars (screeds, adhesives, repair etc.). and for bonding slurries

HEALTH & SAFETY

In case of contact with skin or eyes, rinse thoroughly with water. If irritation persists, seek medical attention. If swallowed, do not induce vomiting and seek medical attention. paste. Use surface adhesion

QUALITY STATEMENT

All our products are manufactured to comply with our internal QA/QC program and quality management system to ensure consistency and quality

DISCLAIMER

While the company guarantees its products against defective materials, the use and application of these products are made without guarantee since the conditions of their applications are beyond its control. It is recommended to verify with the company that the product is suitable for the intended use, and that the Data Sheet version is the latest one. The company may modify it without prior notice. Technical characteristics are listed for guidance only. For more information, please contact the company's office.

NOTE

The information included on this Technical Data Sheet is the sole property of Reckon Chemicals Pvt Ltd. The unauthorized disclosure, use, dissemination or copying (either whole or partial) of this data sheet or any information it contains, is prohibited and subject to legal pursuit.

WARRANTY: The Reckon Chemicals (Pvt.) Ltd. (Reckon) solely and expressly warrants that its products shall be free from defects in materials and workmanship for one (1) year from the date of purchase. Unless authorized in writing by an officer of Reckon, no other representations or statements made by Reckon or its representatives, in writing or orally, shall alter this warranty. Reckon MAKES NO WARRANTIES, IMPLIED OR OTHERWISE, AS TO THE MERCHANTABILITY OR FITNESS FOR ORDINARY OR PARTICULAR PURPOSES OF ITS PRODUCTS AND EXCLUDES THE SAME. If any Reckon product fails to conform with this warranty, Reckon will replace the product to Buyer. Replacement of any product shall be the sole and exclusive remedy available and buyer shall have no claim for incidental or consequential damages. Any warranty claim must be made within one (1) year from the date of the claimed breach. Reckon does not authorize anyone on its behalf to make any written or oral statements which in any way alter Reckon's installation information or instructions in its product literature or on its packaging labels. Any installation of Reckon products which fails to conform with such installation information or instructions shall void this warranty. Product demonstrations, if any, are done for illustrative purposes only and do not constitute a warranty or warranty alteration of any kind. Buyer shall be solely responsible for determining the suitability of Reckon's products for the Buyer's intended purposes.

RECKON CHEMICALS PRIVATE LIMITED
21 CCA, BLOCK B, KHAYABAN-E-AMIN, LAHORE
Toll: +92-42-35452620, +92-42-35230419
Web: www.reckonchemicals.com
Email: Info@reckonchemicals.com

